



Texol Texotherm™ HT Series

Technical Data Sheet

Texol Texotherm™ HT Series

-high performance synthetic heat transfer fluid

Product Description

Texotherm™ HT series are high performance synthetic heat transfer fluid, formulated to operate over a wide temperature range, from -52°C up to +340°C, where it gives excellent oxidation stability and deposit-free operation.

Texotherm™ HT series provides a long service life in closed heat transfer systems. Its low pour point provides energy-efficient start-up and good pumpability in sub-zero ambient temperatures, where pipes or expansion tanks may be sited outdoors.

Customer benefits

- High temperature oxidation stability at +340°C ensures clean, deposit-free system performance
- Dissolves existing system deposits and goes on to maintain system cleanliness, improving uptime
- Extremely low pour point provides easy pumpability and energy-efficient low temperature start-up
- Long fluid service life reduces maintenance downtime and saves Money

Applications and Uses

- Texotherm™ HT series are recommended for indirect heat transfer in closed systems operating in a wide range of applications, such as chemical, leather, textile, rubber, chipboard, food, building materials and fodder processing operations. It is also suitable for use in laundries.
- Within its wide operating temperature range Texotherm HT series can also be used in cooling applications for the removal of process heat.
- Optimum operating temperature range: -52 to +340°C
Maximum use temperature: +340°C
Maximum film temperature: +370°C



Texol Texotherm™ HT Series

Technical Data Sheet

Texol Texotherm™ HT Series

High performance synthetic heat transfer fluid

Typical Properties

Property (Unit)	HT 15	HT 22	HT 32	HT 46	HT 68	Method
Density at +15 °C	0.875	0.881	0.887	0.890	0.895	ASTM D4052
Viscosity @40°C, cSt	15	22	32	46	68	ASTM D445
Viscosity @100°C, cSt	3.06	3.81	5.76	6.85	8.92	ASTM D445
Viscosity Index	126	129	131	134	138	ASTM D2270
Flash Point, °C	>200	>200	>210	>210	>230	ASTM D92
Auto Ignition, °C	349	349	349	349	349	ASTM E659
Pour Point, °C	<-52	<-47	<-45	<-42	<-40	ASTM D97

Technical Expertise

Texol experts on Texol Texotherm™ HT series lubricants are regionally located to respond to your needs. Whether you have a question about products, applications or regulations, Texol offers comprehensive customer and technical service.



The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can no be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.